

AMBULANCE

Features

- Standard Fitments
- Soft suspension provides a quiet and comfortable ride
- Infection carrying items such as spare tyres are housed outside patient compartment
- Full standing height for movement of doctors/attendants with comfortable seating arrangement
- Water bottle stand

Model	Ambulance BS – III	Ambulance BS-IV
Engine & Displacement	SLT3 & Numeral , 3455 cc	SLT4 & Numeral , 3455 cc
Туре	In line 4-Cylinder Direct Injection	In line 4-Cylinder Common Rail Direct Injection
	Diesel Turbo Charger with Intercooler	
Max.Engine Output	75 Kw @3000 rpm	75 Kw @2800 rpm
Max. Torque	270Nm@1750-2000 rpm	296Nm @ 1500 rpm
Clutch	Single plate Diaphragm Type , Dia. 260mm	
Gear Box	Synchromesh Manual 5-Forward and 1-Reverse	
Steering	Mechanical /Power Steering (Optional)	
Brakes	Hydraulic Vaccume assisted	
Suspension	Semi Elliptical Type Multi Leaf Spring	
Min. Ground clearance (mm)	206	
Wheel & Tyres	6+1	4+1
Wheelbase (mm)	2515	2815
Min. Turning Circle Diameter (m)	5	5.5
Front Axle Weight (kg)	2400	2580
Rear Axle Weight (kg)	3800	3160
Max. Permissible GVW (kg)	6200	5740
Fuel Capicity (Its)	90	90
DIMENSIONS		
Overall Length	4919	5479
Overall Width	2100	2100
Overall Height	2725	2752
Optional Fitments	Air Conditioning	







Features

Standard Fitments

Soft suspension provides a quiet and comfortable ride

Infection carrying items such as spare tyres are housed outside patient compartment

Full standing height for movement of doctors/attendants with comfortable seating arrangement

Water bottle stand

Glucose stand

Lower berth

Siren

Top light

Fire Extinguisher

Sterilizer pack

Oxygen cylinder bracket

Exhaust Fan

Room Light

Upper berth

Switch board

Water tank

Wash basin

Fans

First Aid Box